

SAFETY INFORMATION for G-WENDT PRODUCTS

By purchasing one of our products, you have chosen the highest quality!

GENERAL

Please inspect machines and products for any damage prior to use. Do not use damaged machines and products under any circumstances!

- · Ensure proper handling and storage
- Follow instructions on carton and product labels
- · Observe restrictions on use
- Avoid vibrations
- Dispose of in accordance with regional/national regulations



Follow instructions



Cutting not permitted / 90°



Wear ear protection



Side grinding not permitted



Wear eye protection



Do not use damaged discs



Wear a mask



Wear ear, eye and mouth protection



Wear gloves



Use only with support plates



Cutting permitted



Side grinding permitted

WORKING WITH CUTTING DISCS AND GRINDING TOOLS

Make sure that the tool is always kept in good condition

- Only use vulcanised fibre discs, unmounted flap wheels, abrasive flap discs and flap wheels certified to EN 13743
- Only use cutting and grinding discs certified to EN 12413
- Do not use cutting and grinding discs that have exceeded their expiration date
- Do not exceed maximum RPM rating maximum working speed
- · Proper installation of the grinding tool is essential
- Only use suitable clamping flanges/clamping devices
- · Follow instructions on the direction of rotation
- Ensure that the workpiece is secured firmly in place
- Tie back long hair; do not wear loose clothing or jewelry
- Fix tools properly
- Avoid jamming/pinching as this can result in serious injury
- · Avoid excessive contact pressure
- All dry grinding work must be carried out using a suitable extraction system
- Do not modify the products in any way
- Ensure even handling of the grinding tool
- Only use a grinding tool that is suitable for the intended use

USE OF MACHINES

- Do not remove or modify machine safety equipment
- · Maintain control of the machine
- Disconnect the machine from power source when replacing accessories
- Make sure the machine is fully stopped before it is set down